



D4720-1 SPACER

NOTES:

- 1) MATERIAL: 6061-T4/-T42 SEAMLESS ALUMINUM TUBING PER WW-T-700/6, AMS 4081, OR ASTM B210 / B221 / B241
REF DART SPEC M6061T4T0.375W.058
OR
6061-T6/-T62/-T6510/-T6511 SEAMLESS ALUMINUM TUBING PER WW-T-700/6, QQ-A-200/8, QQ-A-225/8, AMS 4080 OR
AMS 4082 OR AMS 4083, OR ASTM B210 / B221 / B241
REF DART SPEC M6061T6T0.375W.58
HEAT TREAT TO -T4/-T42 CONDITION. MIN UTS = 30 KSI (60 HREW MIN)

- 2) FINISH: NONE
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: NONE
- 7) WEIGHT: 0.02 lbs

RELEASED
2017-08-11
ECN 17-615

APPROVED

B	CORRECT MAT'L CALLOUT PER M6061T6T: ADD "SEAMLESS", "T6510", "T6511", "AMS4083", 3.250 DIM WAS 3.180, REASON PAR15-444	SAD	17.01.26
A	NEW ISSUE	RP	12.09.10
REV.	DESCRIPTION	BY	DATE
DESIGN	RP	DART AEROSPACE USA, INC. EUGENE, OR	
DRAWN	SAD		
CHECKED	WM	DRAWING NO. D4720	
MFG. APPR.	DD	REV. B SHEET 1 OF 1	
APPROVED	CP	TITLE SPACER	
DE APPR.	N/A	SCALE NTS	
DATE	17.01.26	<small>COPYRIGHT © 2012 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.</small>	